



\*Imagen de referencia.

## GU50PS

60Hz@1800RPM 220/127V 3PH

### Overall Performance

PRP Continuous Power kVA	50
PRP Continuous Power kW	40
LTP Stand-by power kVA	55
LTP Stand-by power kW	44
Power factor cos φ	0.8
Voltage VAC	208/120
Frequency Hz	60
Ampere PRP/LTP	132/146
Speed RPM	1800

# GU50PS

### Overall Performance

Length mm	2220
Width mm	960
Height mm	1258
Net Weight kg	1247
Gross Weight kg	-
Sound pressure at 7 mt dBA	67.00

#### Silent generator with following specifications:

##### Frame:

- Heavy duty fabricated welded base plate with high quality steel UNIS235 JR.
- Heavy duty, bell type, rubber anti-vibration mountings
- Fuel tank with drain plug and retention basin
- Feet and four lifting holes on the base
- Oil draining mechanical pump

##### Canopy:

- Four large doors for easy access for service and maintenance
- Electro-galvanized sheet DC01+ZE25/25(EN10152:2009)
- High precision sheet cutting with nitrogen laser technology to avoid oxidation.
- Sandblasting and cataphoresis treatment of intake / exhaust grids
- Weatherproof sealed joints
- Lockable handles in each door
- RAL 9010 "orange peel" specific powder coat paint for outdoor usage
- Rain cap on exhaust outlet
- Coolant refilling specific hatch
- Fuel filter outside enclosure
- Ecological Sound foam: 100% Recyclable, 35 mm thickness, fire proof self-extinguishing class1 fire-reaction compliant washable, mechanically fixed to the frame

##### Muffler:

- Residential type
- Integrated in the canopy
- With aluminum coating

##### Control Panel:

- Metal control panel with protective back cover
- Dedicated area to make easier the electrical connection to the load

All units and components are prototype tested, factory build and production tested. A specific control procedure during the several stages of production ensures long life and reliability.

# GU50PS

60Hz@1800RPM 220/127V 3PH

## Engine general data

Engine brand	Perkins
Model	1103A-33TG1
PRP Power kW	48.80
LTP Power kW	53.90
Fuel	Diesel
Nr. cylinders	3
Air intake	Turbocharged
Cooling	Water
Cubic capacity l	3.30
Speed regulation	Mechanical
Performance Class - steady state regulator accuracy +/- %	G2 - 0.75
Load Step G1 - KWe	-
Load Step G2 - Kwe	-
Load Step G3 - KWe	-
Voltage VDC	12
Emissions	-

## Alternator general data

Alternator Brand	Stamford
Model	S1L2-N1
Type of excitation	Self-excited
Type of regulation	AVR
Regulator precision +/- %	1.00

## Structure data

Type of structure	STRONG
Tank capacity l	100
Retention basin	Yes
Exhaust diameter mm	50

# SOLDEPYE

## Fuel Consumption

Consumption 25% l./h	4.30
Consumption 25% l./h	7.10
Consumption 25% l./hr	9.90
Consumption 25% l./h	12.90
Autonomy at 75% of load h.	=10 h

## Engine liquids and equipment

Type of lubricant	Oil SAE 15W40
Lubrication capacity l.*	8.30
Type of coolant	Antifreeze liquid
Coolant capacity l.*	10.20
Air intake filter	Paper cartridge
Battery capacity Ah.	70
Number of batteries*	1

## Fuel system and energy balance

AC pump suction head kPa	2
Combustion air flow volume LTP m3/min	3.90
Cooling air capacity LTP m3/min	70.00
Exhaust gas flow flow-density LTP m3/min	9.50
Exhaust gas temperature LTP °C	551.00
Brake mean effective pressure kPa	15.00
Energy to exhaust LTP kWt	43.00
Energy to coolant LTP kWt	34.00
Energy to radiation LTP kWt	9.00



\*Imagen de referencia.



## Control panel features



**DSE-4520**



\*Imagen de referencia.

Protection cover  
Circuit breaker  
AMF controler DSE4520

- Voltmeter, frequencymeter, Ammeter
- Generator power (kW, kV, Ar, kV A & pf) monitoring.
- Hour meter
- Fuel level meter
- Overland (kW & kV Ar) protection
- Low oil pressure protection
- Higt coolant temperature protection

- Low fuel level protection
- Battery charger alternator fault
- Rpm protector


Emergency stop button  
Terminal board for ATS connection  
Battery charger  
On/off switch

## Data reference

Standard reference conditions temperature 25 °C, altitude 1-1000m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0,8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0,850 gr/lt. Power performance data as quoted can be obtained after the initial running-in period of the engine, during which one has to follow the instructions of the engine manufacturer as stated in the use and maintenance manual of the specific engine. The tolerance shown by the engine manufacturer is +/-5%. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accesories can modify weight, dimensions, performance, P.R.P. Prime power-continuous power at variable load: The power that a genset can supply in continuous service at variable load for an any number of hours per year while respecting the maintenance intervals established in the envirometal conditions stated by the Manufacturer. according to ISO8528-1. The average power supplied over time over time and any the maintenance intervals established in the environmental conditions stated by the Manufacturer according to ISO 8528-1. The number of hours per year is stated by the Manufacturer. Overload is not permitted. \*For reasons of transport and/or Storage, liquids(oli and antifreeze) and batteries not be included in the delivery.



# SOLDEPYE



# 24 HORAS



## ¡Hablemos!